

**PVC 包塑金属软管/PVC coated metallic flexible conduit**

**材质:** PVC 包塑 + 镀锌钢带、PVC 包塑 + 不锈钢带

**耐温范围:** -10°C---+80°C

**应用:** 工业机器人, 电力发电, 轨道交通, 通信系统, 工业自动化设备。

**产品特点:** 1. 热镀锌钢带及特殊防腐处理。

2. 柔软及良好的弯曲性能, 高抗拉强度, 不易折断和变形。


**Material:** PVC coated + galvanized steel strip, PVC coated + stainless steel 304 strip

**Temperature range:** -10°C---+80°C

**Application:** industrial robots, power generation, rail transportation, communication system, industrial automation equipment, lighting equipment.

**Features:** 1. Hot-dipped galvanized steel strip with special anti-corrosion treatment.

2. PVC surface thickened layer, having super soft and excellent bending performance, strong tensile resistant, not easily broken or deformed.



型号 Part No.		规格 Normal Size		外径 O.D	自然弯曲 Natural Curve	包装 Packing
镀锌钢带(GI)	不锈钢带(S.S)	Inch	mm	mm	mm	m/roll
MYW-VJ3S06	MYW-VJ3SS06	3/16"	φ6	8.8±0.25	40	200/100
MYW-VJ3S08	MYW-VJ3SS08	1/4"	φ8	11.3±0.30	45	100
MYW-VJ3S10	MYW-VJ3SS10	5/16"	φ10	14.8±0.30	55	100
MYW-VJ3S12	MYW-VJ3SS12	3/8"	φ12(13)	16.5±0.35	65	100
MYW-VJ3S15	MYW-VJ3SS15	1/2"	φ15(16)	20.3±0.35	85	100
MYW-VJ3S20	MYW-VJ3SS20	3/4"	φ20	24.3±0.40	100	50
MYW-VJ3S25	MYW-VJ3SS25	1"	φ25	29.5±0.45	120	50
MYW-VJ3S32	MYW-VJ3SS32	1-1/4"	φ32	37.8±0.50	150	25
MYW-VJ3S38	MYW-VJ3SS38	1-1/2"	φ38	44.7±0.60	180	25
MYW-VJ3S51	MYW-VJ3SS51	2"	φ51	58.2±1.00	220	20
MYW-VJ3S64	MYW-VJ3SS64	2-1/2"	φ64	71.4±1.50	310	20
MYW-VJ3S75	MYW-VJ3SS75	3"	φ75	85.6±2.00	350	20
MYW-VJ3S100	MYW-VJ3SS100	4"	φ100	111.0±3.00	410	10