

铜镀镍电缆接头/Nickel plated brass cable gland**材质:** 铜镀镍**耐温范围:** -40°C---+110°C (静态); -20°C---+80°C (动态)**防护等级:** IP68 (在规定的卡口范围内, 使用"O"型圈并旋紧迫紧头)**螺纹标准:** PG (德制)、M (公制)、G (英制)**Material:** nickel plated brass**Temperature range:** -40°C---+110°C(Static); -20°C---+80°C(Dynamic)**Protection rating:** IP68(Within clamp range, using "O" ring and screw tight the pressing fastener.)**Thread standard:** PG, G, metric

型号 Part No.	螺纹标准 Thread standard	卡口范围(mm) Clamp range(mm)
MYW-CGB-PG7	PG7	3-6.5
MYW-CGB-PG9	PG9	4-8
MYW-CGB-PG11	PG11	5-10
MYW-CGB-PG13.5	PG13.5	8-12
MYW-CGB-PG16	PG16	10-14
MYW-CGB-PG21	PG21	13-18
MYW-CGB-PG29	PG29	18-25
MYW-CGB-PG36	PG36	25-32
MYW-CGB-PG42	PG42	32-38
MYW-CGB-PG48	PG48	37-44
型号 Part No.	螺纹标准 Thread standard	卡口范围(mm) Clamp range(mm)
MYW-CGB-G1/4	G1/4"	3-6
MYW-CGB-G3/8	G3/8"	4-8
MYW-CGB-G1/2	G1/2"	8-12
MYW-CGB-G3/4	G3/4"	13-18
MYW-CGB-G1	G1"	15-22
MYW-CGB-G1-1/4	G1-1/4"	22-28
MYW-CGB-G1-1/2	G1-1/2"	25-32
MYW-CGB-G2	G2"	37-44

型号 Part No.	螺纹标准 Thread standard	卡口范围(mm) Clamp range(mm)
MYW-CGB-M12	M12*1.5	3-6
MYW-CGB-M14	M14*1.5	3-6
MYW-CGB-M16	M16*1.5	4-8
MYW-CGB-M18	M18*1.5	6-10
MYW-CGB-M20	M20*1.5	8-12
MYW-CGB-M22	M22*1.5	10-14
MYW-CGB-M24	M24*1.5	10-14
MYW-CGB-M25	M25*1.5	10-14
MYW-CGB-M27	M27*2.0	13-18
MYW-CGB-M30	M30*2.0	13-18
MYW-CGB-M32	M32*1.5	15-22
MYW-CGB-M33	M33*2.0	15-22
MYW-CGB-M36	M36*2.0	18-25
MYW-CGB-M40	M40*1.5	18-25
MYW-CGB-M42	M42*2.0	22-28
MYW-CGB-M48	M48*2.0	25-32
MYW-CGB-M50	M50*1.5	25-32
MYW-CGB-M54	M54*2.0	32-38
MYW-CGB-M56	M56*2.0	32-38
MYW-CGB-M60	M60*2.0	37-44
MYW-CGB-M63	M63*1.5	37-44
MYW-CGB-M64	M64*2.0	37-44
MYW-CGB-M72	M72*2.0	42-52
MYW-CGB-M80	M80*2.0	50-60
MYW-CGB-M85	M85*3.0	59-72
MYW-CGB-M100	M100*2.0	71-82